

**MCGINN & GIBB, P.C.**  
**A PROFESSIONAL LIMITED LIABILITY COMPANY**  
**PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW**  
**1701 CLARENDON BOULEVARD, SUITE 100**  
**ARLINGTON, VIRGINIA 22209**  
**TELEPHONE (703) 294-6699**  
**FACSIMILE (703) 294-6696**

**APPLICATION  
FOR  
UNITED STATES  
LETTERS PATENT**

**APPLICANT:** MASATAKA MITAMA  
**FOR:** SOFTWARE PORTABLE TELEPHONE SET  
**DOCKET NO.:** 11P083162

## SOFTWARE PORTABLE TELEPHONE SET

BACKGROUND OF THE INVENTION

The present invention relates to a software portable telephone set and, more particularly, to a software portable telephone set capable of coping with a plurality of different radio systems with the same hardware structure by emitting reconfiguration afresh and also mounting and demounting for each system.

In a software radio unit, signals which are received and to be transmitted are converted in an A/D and D/A converters from analog to digital signal and vice versa, respectively, so that digital signal processing is performed as much as possible in the radio unit. Digital signal processing is performed according to a software program. This means that the content or function of the signal processing can be changed by replacing the software. It is thus possible to readily cope with a plurality of different radio systems with the same hardware structure by changing programs.

However, when it is intended to apply such software radio techniques to portable telephone sets, the following problem is encountered. To be able to cope with a plurality of different systems, wide-band active and passive components are necessary. Usually, the expanding the frequency band coverage of components results in characteristics deterioration. Particularly, deterioration of the transmission side characteristics due to frequency band coverage increase

directly influences the performance of the portable telephone set, and this is a great barrier in the realization of software portable telephone sets.

While the above software radio techniques require  
5 wide-band passive and active components to be able to cope with a plurality of different systems. Usually, the characteristics of the active and passive components are deteriorated with frequency band coverage increase. Particularly, it is really difficult to maintain high  
10 efficiency of a transmitting power amplifier, which is one of the main function components of the transmitting side part, over a wide frequency band. It is also really difficult to increase, with low loss, the frequency band coverage of transmission signal filters and isolators.  
15 Deterioration of characteristics of the transmission side components poses problems in the portable telephone set that allowed time of use is reduced and that the size of the portable telephone set body is increased, thus greatly spoiling the commercial value of the software  
20 portable telephone set.

#### SUMMARY OF THE INVENTION

The present invention has been for solving the above drawback, and it has an object of providing a software portable telephone set, which have resort to  
25 reconfigurable circuit techniques to be able to cope with a plurality of different systems while holding the same hardware structure and permit, with a detachable transmitting function, the selection of best performance

power amplifier and other components for each system,  
so that it is suited for frequency band coverage increase.

According to an aspect of the present invention,  
there is provided a software portable telephone set  
5 comprising a detachable transmitting function and  
transmitting and receiving circuits capable of being  
reconfigured afresh with software updating, wherein the  
transmission system is reconfigured afresh in relation  
to the mounting and demounting of a transmitting function  
10 part. According to the above invention, it is possible  
to provide a transmission part suitable to each system.  
Further, a wide range bandwidth transmission and  
reception operations are possible by coping with a  
plurality of systems with the same hardware  
15 construction.

The transmitting function is provided by a  
detachable module for transmitting a modulator output  
analog signal. According to this, it is possible to  
select an optimum module for each system to realize an  
20 optimum transmission without degrading the  
characteristic of the transmission parts.

The transmitting and receiving circuits have a  
software memory part for executing signal conversion  
processing, programs transferred from a program memory  
25 being set in the software memory part. According to this,  
it is possible to easily cope with a plurality of systems  
with the same construction.

The transmitting and receiving circuits include a

demodulator, a modulator and wide-band synthesizer which are controlled by a program stored in the software memory part. According to this, it is possible to cope with a plurality of systems with the same construction by  
5 controlling the demodulator, modulator and wide-band synthesizer with a program corresponding to each system, with the same construction.

The detachable module includes a power amplifier, a transmission signal filter and an isolator. According  
10 to this, it is possible to select an optimum module for each system, thus preventing the degradation of the characteristic of the power amplifier, transmission signal filter and isolator. Further, since the character deterioration is caused the characteristic  
15 with low loss can be maintained and the deterioration of the parts is prevented.

The transmitting and receiving circuits have a software memory part for executing signal conversion processing, programs transferred from a program memory  
20 being set in the software memory part and a plurality of programs for commanding signal conversion processing are stored in the program memory. According to this, it is possible to can cope with a plurality of systems by storing a plurality of programs and cope with a service  
25 in a district corresponding to the movement of portable telephone set.

The transmitting and receiving circuits have a software memory part for executing signal conversion

processing, programs transferred from a program memory  
being set in the software memory part and the software  
memory provides commands according to a program  
transferred from the software source memory according  
5 to a system switching command. According to this, it is  
possible to cope with each system by the program command.

According to an aspect of the present invention,  
there is provided a portable telephone set comprising  
a transmission function unit and/or a receipt function  
10 unit, wherein the transmission function unit for  
performing a specified transmission process is  
detachably mounted to a body of the portable telephone  
set and the operation of the transmission function and/or  
receipt function is determined on the basis of a  
15 predetermined software which is selected.

The predetermined software is selected from a  
plurality of softwares stored in a memory in the portable  
telephone set.

The operation of a received signal mixing portion,  
20 a demodulating portion and a base band signal processing  
portion in the receipt function unit is determined on  
the basis of the predetermined software.

One of a plurality of transmission function units  
each performing a different frequency band operation is  
25 detachably mounted to the body.

The plurality of softwares are stored in a software  
source memory, one of the plurality of softwares is  
selected and down-loaded and the operation of the receipt

processing unit is defined by the down-loaded software.

The transmission function unit includes an amplifier, a transmission signal filter and an isolator.

The transmission function unit includes a software  
5 memory for storing a plurality of softwares each adapted to each transmission function unit, the predetermined software is defied by loading the software from the software memory in the mounted transmission function unit.

10 Currently operation system is detected on the basis of demodulated output of the received signal in the receipt function unit and the detected system is displayed.

Other objects and features will be clarified from  
15 the following description with reference to attached drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing a first embodiment of the present invention;

20 Fig. 2 is a block diagram showing a second embodiment of the present invention;

Fig. 3 is a block diagram showing a third embodiment of the present invention; and

25 Fig. 4 is a flow chart illustrating the operation of the system detector unit 60.

#### PREFERRED EMBODIMENTS OF THE INVENTION

Preferred embodiments of the present invention will now be described with reference to the drawings.

An embodiment of the present invention will now be described with reference to the drawings. The embodiment to be described is merely an example of the software portable telephone set according to the present invention.

As shown in Fig. 1, in the software portable telephone set according to the present invention a received signal inputted from an antenna 1 is fed through a received signal mixer 2 and an A/D converter 3 to a demodulator 4. The demodulator 4 is operated according to software down-loaded in a software memory 5. The function of the demodulator 4 can be reconfigured afresh with every software updating.

The down-loaded software is preliminarily stored in a software source memory 6 which is programmed for each system. In other words, a plurality of software entities are stored in the software source memory 6, and one of them is selected and down-loaded in the memory 5 by a software switching controller 5a. The received signal mixer 2 receives a local oscillation signal fed from a wide-band synthesizer 7 with the frequency thereof restricted according to the software. As a result of the demodulation, a digital signal is fed to a baseband signal processor 8 for signal processing, and then fed out through a man-machine interface 9 to the outside. The base-band signal processor 9 can be reconfigured afresh according to the software. On the transmission side, voice or like signal is inputted along a route converse



to that of the received signal to a modulator 10. The modulator 10, like the reception side, can be reconfigured afresh for each system according to software.

5       The modulator output is fed to a D/A converter 11 for conversion to an analog signal. The analog signal is fed to a transmission signal mixer 12 for conversion to a carrier frequency, and then fed to a module 20, which includes a power amplifier 21, a transmission signal  
10 filter 22 and an isolator 23, to be sent out via the antenna 1. A plurality of modules (20, 30 and 40) are prepared each for each system such as frequency band and used detachably. Since the modules are detachable, it is possible to select best module components such as power  
15 amplifier as for each system. It is thus possible to avoid characteristic deterioration due to frequency band increase.

Fig. 2 is a block diagram showing a second embodiment of the present invention. This embodiment is  
20 the same as the previous first embodiment except for that the modules 20, 30 and 40 include respective program memories 24, 34 and 44, in which software for corresponding systems is stored. When a module is mounted, the software thereof is down-loaded in the  
25 software memory 5. In this embodiment, the software source memory 6 in the previous first embodiment can be dispensed with, which is desired for reducing the price and size of portable telephone sets.

Fig. 3 is a block diagram showing a third embodiment of the present invention. This embodiment is the same as the previous first embodiment except for that a system detector unit 60 and a system display unit 70 are provided on the transmission side. Fig. 4 is a flow chart illustrating the operation of the system detector unit 60. In Fig. 4, the power of portable telephone set is "on", then a software n ( $n=1$  to  $n$ ) from a software memory 6 is down-loaded (step S1). Next, the system detector 60 checks whether the output of demodulator exists or not (step S2). When no demodulator output is checked the routine is ended. When the demodulator output exists, a display signal for displaying the system n is generated (step S3) and the routine is ended.

From a display obtained as a result of detection, the user can know systems which can be presently used. Thus, a module complying with the display may be selected and mounted. Thus, even in an unfamiliar land or the like, a system offering services can be known, and communication can be readily set.

As has been described in the foregoing, with the software portable telephone set according to the present invention, it is possible to avoid characteristic deterioration of transmission side components with a detachable transmitting function, and also the transmitting and receiving circuits which are capable of being reconfigured afresh permits coping with a plurality of systems with the same hardware structure.

It is thus possible to provide a software portable telephone set, which is suited for frequency band coverage increase.

Changes in construction will occur to those skilled  
5 in the art and various apparently different modifications  
and embodiments may be made without departing from the  
scope of the present invention. The matter set forth in  
the foregoing description and accompanying drawings is  
offered by way of illustration only. It is therefore  
10 intended that the foregoing description be regarded as  
illustrative rather than limiting.